



TAILIN®

Flexible Offset Grinding Wheels



TAILIN TOUCH A semi-flexible type 27 depressed center grinding wheels that can be used for polishing, light weld grinding and de-scaling with right angle grinders.

TAILIN TOUCH will allow you to put more grinding surface to the job, resulting in faster stock removal and smoother finish. Flexible wheel will avoid operator fatigue usually due to the vibraton.

APPLICATION

- A : Ferrous metals (steel, iron, welds, etc.)
- WA : Stainless steel, alloy steels.
- CC : Non-ferrous metals
(aluminum, copper, cast iron and stone)
- GC : Glass, ceramic.

GRIT SIZE

- #24, #36, #46, #60, #80, #100, #120, #150, #220

« 4-1/2", 5", 7" & 9" With 5/8-11 Hub Are Available Upon Request. »

SIZE		MAX. R.P.M.		STANDARD PACKING			N.W.	G.W.	MESMT
mm	inches	4,300/MIN	4,800/MIN	PCS/SINGLE	PCS/INNER BOX	PCS/CARTON	KGS/CARTON	KGS/CARTON	CFT
100x2x16	4x3/32x5/8	13,700		20	200	600	24.6	26.8	1.78
100x3x16	4x1/8x5/8		15,300	20	200	600	30.0	32.2	1.78
115x3x22	4 1/2x1/8x7/8		13,300	25	100	400	26.4	29.3	1.41
125x3x22	5x1/8x7/8		12,200	25	100	400	30.8	33.3	1.43
180x2x22	7x3/32x7/8	7,600		25	50	200	22.2	24.8	1.17
180x3x22	7x1/8x7/8		8,500	25	50	200	32.8	35.1	1.61
230x3x22	9x1/8x7/8		6,600	25	50	100	28.1	29.6	1.10

